

PTO/SB/21 (05-03)

Approved for use through 04/30/2003. OMB 0651-0031

U.S. Patent and Trademark Office; U.S. DEPARTMENT OF COMMERCE

Under the Paperwork Reduction Act of 1995, no persons are required to respond to a collection of information unless it contains a valid OMB control number.

3676

TRANSMITTAL FORM (to be used for all correspondence after initial filing)	Application Number	09/937,083
	Filing Date	September 21, 2001
	First Named Inventor	Hofmann, Knut
	Art Unit	3676
	Examiner Name	Patel, Vishal A.
Total Number of Pages in This Submission	Attorney Docket Number	85934.000008

ENCLOSURES (check all that apply)		
<input type="checkbox"/> Fee Transmittal <input type="checkbox"/> Fee Attached <input checked="" type="checkbox"/> Amendment/Reply <input type="checkbox"/> After Final <input type="checkbox"/> Affidavit/declaration(s) <input type="checkbox"/> Extension of Time Request <input type="checkbox"/> Express Abandonment Request <input type="checkbox"/> Information Disclosure Statement <input type="checkbox"/> Certified Copy of Priority Document(s) <input type="checkbox"/> Response to Missing Parts/Incomplete Application: <input type="checkbox"/> Response to Missing Parts Under 37 CFR 1.52 or 1.53	<input type="checkbox"/> Drawing(s) <input type="checkbox"/> Licensing-related Papers <input type="checkbox"/> Petition <input type="checkbox"/> Petition to Convert to a Provisional Application <input type="checkbox"/> Power of Attorney, Revocation Change of Correspondence Address <input type="checkbox"/> Terminal Disclaimer <input type="checkbox"/> Request for Refund <input type="checkbox"/> CD, Number of CD(s) _____	<input type="checkbox"/> After Allowance communication to Group <input type="checkbox"/> Appeal Communication to Board of Appeals and Interferences <input type="checkbox"/> Appeal Communications to Group (Appeal Notice, Brief, Reply Brief) <input type="checkbox"/> Proprietary Information <input type="checkbox"/> Status Letter <input checked="" type="checkbox"/> Other Enclosure(s) (please identify below): English Translation (11 pages); Certificate of Translation (1 page)
Remarks		RECEIVED DEC 30 2003 GROUP 3600

SIGNATURE OF APPLICANT, ATTORNEY, OR AGENT	
Firm or Individual name	Thomas B. Ryan, Registration No. 31,659 HARTER, SECREST & EMERY LLP
Signature	
Date	December 18, 2003


CERTIFICATE OF TRANSMISSION/MAILING			
I hereby certify that this correspondence is being deposited with the United States Postal Service with sufficient postage as first class mail in an envelope addressed to: Mail Stop Non-Fee Amendment, Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450 on the date shown below.			
Type or printed name	Paula Weil		
Signature		Date	December 18, 2003

This collection of information is required by 37 CFR 1.5. The information is required to obtain or retain a benefit by the public which is to file (and by the USPTO to process) an application. Confidentiality is governed by 35 U.S.C. 122 and 37 CFR 1.14. This collection is estimated to take 12 minutes to complete, including gathering, preparing, and submitting the completed application form to the USPTO. Time will vary depending upon the needs of the individual case. Any comments on the amount of time you are required to complete this form should be sent to the Chief Information Officer, U.S. Patent and Trademark Office, U.S. Department of Commerce, P.O. Box 1450, Alexandria, VA 22313-1450. DO NOT SEND FEES OR COMPLETED FORMS TO THIS ADDRESS. SEND TO: Commissioner for Patents, P.O. Box 1450, Alexandria, VA 22313-1450.

If you need assistance in completing the form, call 1-800-PTO-9199 (1-800-786-9199) and select option 2.

I, Julia Schraplau, translator with FLÜGEL PREISSNER KASTEL declare that I am familiar with the German and English languages and that the accompanying translation of the **priority document No. 199 13 105.8 – Germany – March 23, 1999** has been prepared by me and that it is a true translation to the best of my knowledge and ability.

This day October 20, 2003


(Signature)

BEST AVAILABLE COPY

Shaped Seal for Sealing a Power-Operated Closing Device

The present invention relates to a shaped seal or sealing profile for weather-sealing a powered closing device, including an anti-trap guard comprising at least two electrically conductive portions spaced away from each other, whose contact activates a switching action for activating the drive assembly of the closing device in which at least one of these portions is electrically conductive connected to a metallic conductor to reduce the volume resistivity.

A generic sealing profile is known from DE 197 20 713 C1 originated to the same Applicant. This known sealing profile comprises two electrically conductive portions spaced away from each other, in each of which a metallic conductor is embedded to reduce the volume resistivity. The disadvantage in making use of these two metallic conductors is that they take up a lot of room, relatively, and add to the price and weight of the sealing profile whilst complicating production since both metallic conductors need to be coextruded.

It is thus the objective of the present invention to sophisticate a generic sealing profile to achieve cost-effective production for a low price, weight and space requirement.

In accordance with the invention this objective is achieved for a generic sealing profile in that the metallic conductor is configured as a carrier for securing the sealing profile and/or as a flange or frame to which the sealing profile is securable.

The sealing profile in accordance with the invention now makes it possible to totally eliminate a metallic conductor as needed hitherto. Instead of this, recourse is made to the carrier of the sealing profile existing in many cases. This carrier is, as a rule, made of a light metal and is thus electrically conductive. As an alternative, or in addition thereto, a flange or frame may be used to which the sealing profile is securable. This flange or frame is already available,

especially in automotive applications, and is made of an electrically conductive metal. Due to totally eliminating one of the metallic conductors as needed hitherto, the production of the sealing profile in accordance with the invention is substantially simplified, with a further reduction in price and weight, as well as reducing the space requirement.

Advantageous aspects and further embodiments read from the dependent claims.

In a first advantageous aspect the carrier contacts the electrically conductive portion. In this case the electrically conductive portion is arranged only on one side of the carrier in thus simplifying production.

In a second advantageous aspect the carrier is partly or totally surrounded by the electrically conductive portion in thus enlarging the contact surface area between the electrically conductive portion and the carrier so that the volume resistivity can be further reduced.

In accordance with one further embodiment the carrier is provided with recesses. These recesses reduce the weight of the carrier and permit flexing of the sealing profile. In addition, the recesses permit, for a carrier surrounded partly or fully by the electrically conductive portion, a direct electrically conductive connection from one side of the carrier to the other. This is of advantage when a carrier of an electrically non-conductive material, or a carrier insulated from the electrically conductive portion, is used. The recesses also make it possible in these cases to produce an electrically conductive connection from one side of the carrier to the other.

Advantageously the electrically conductive portion extends up to the outer side of the sealing profile to thus produce an electrical contact with the flange or frame to which the sealing profile can be secured without an additional electri-

cal conductor needing to be provided, i.e. the sealing profile merely requiring to be secured, as usual, to the flange or frame.

In another advantageous aspect, the electrically conductive portion comprises lips or tabs for securing the sealing profile to the flange or frame. These lips or tabs are pressed into contact with the flange or frame to produce a good electrical contact so that the volume resistivity of the sealing profile can be reliably diminished.

In another advantageous further embodiment the anti-trap guard portion comprises a hollow chamber in which at least one of the electrically conductive portions is arranged. Advantageously, one of the electrically conductive portions is arranged at the inner side of the hollow chamber whilst the other protrudes into the hollow chamber to thus achieve a reliable contact between the electrically conductive portions, irrespective of the anti-trap guard.

In yet another advantageous aspect the hollow chamber serves to weatherseal the powered closing device. The anti-trap guard portion of the sealing profile in accordance with the invention then satisfies a dual function whilst eliminating the need for additional elements for weathersealing the closing device in thus further reducing the space requirement and weight as well as the price of the sealing profile in accordance with the invention.

Advantageously the electrically conductive portion, provided separate from the carrier, flange or frame, comprises a metallic conductor, as a result of which the volume resistivity in this portion too is considerably reduced.

The invention will now be detailed by way of example embodiments as shown in the drawing diagrammatically in which:

Fig. 1 is a cross-section through a first embodiment of the sealing profile in accordance with the invention;

- Fig. 2 is a cross-section through a second embodiment of the sealing profile in accordance with the invention;
- Fig. 3 is a cross-section through a third embodiment of the sealing profile in accordance with the invention;
- Fig. 4 is a cross-section through a fourth embodiment of the sealing profile in accordance with the invention; and
- Fig. 5 is a system diagram of the principle involved.

Referring now to Fig. 1 there is illustrated a first embodiment of a sealing profile 10 in accordance with the invention. The sealing profile 10 comprises a clamping portion 11 as well as a sealing portion 12. Further provided is a cover 13 with which components (not shown) are covered after the sealing profile 10 has been secured in place. For securing it in place, the clamping portion 11 comprises a recess 14 into which several lips 15 and protuberances 16 protrude. The recess 14 is clasped by a carrier 17 having a U-shaped cross-section. For securing it in place, the recess 14 of the clamping portion 11 is mounted on a flange as evident from Fig. 5. In this arrangement the lips 15 and protuberances 16 are firmly pressed against the flange in preventing release of the sealing profile 10.

The sealing portion 12 comprises a hollow chamber 18 which at its side facing a window pane 25 is provided with a friction-reducing coating 23, more particularly a flake coating. The window pane 25 is movable in the direction of the arrows 24. When the window pane 25 is closed the hollow chamber 18 is deformed so that the desired weatherseal is furnished.

The sealing profile 10 comprises further an anti-trap guard portion 32. The anti-trap guard portion 32 includes two electrically conductive portions 19, 20 spaced away from each other by an interspace 21. As soon as an object is trapped on closing of the window pane 25, the portion 19 is moved in the direction of the portion 20. Contact of the two portions 19, 20 triggers a switching

action for activating the drive assembly of the window pane 25. This switching action can either halt or reverse the movement of the window pane 25.

The portions 19, 20 are made to advantage by adding an electrically conductive material to the base material of the sealing profile 10 by means of coextrusion. To reduce the volume resistivity the portions 19 comprises a metallic conductor 22. The portion 20 partly surrounds the carrier 17 configured as a metallic conductor, as a result of which the volume resistivity of the electrically conductive portion 20 is likewise diminished. No additional metallic conductor is needed for the portion 20.

In the embodiment as shown in Fig. 1 all electrically conductive components 17, 22 and portions 19, 20 are surrounded by the electrically non-conductive material of the sealing profile 10. The sealing profile 10 is thus electrically neutral as regards its surroundings.

Three further embodiments of a sealing profile 30, 40, 50 in accordance with the invention are shown in Figs. 2 to 4, whereby like or functionally identical components are identified by the same reference numerals as in Fig. 1, for the description of which, reference is made to the above comments to avoid tedious repetition.

Referring now to Fig. 2 there is illustrated how the sealing profile 30 comprises a carrier 27 which is totally surrounded by the electrically conductive portion 20. The carrier 27 is provided with recesses 28 through which the material of the electrically conductive portion 20 penetrates. The contact surface area between the electrically conductive portion 20 and the carrier 27 is substantially increased by the recesses 28. Furthermore, any potential difference can be conducted from one side of the carrier 27 through the recesses 28 to the other side of the carrier 27 solely through the portion 20. Even when not using a non-conductive carrier 27 the inner side and outer side of the carrier 27 are electrically interconnected by the recesses 28.

The electrically conductive portion 20 extends up to the outer side of the sealing profile 30. As soon as the sealing profile 30 is secured to a flange or frame, the lips 15 and protuberances 16 of the clamping portion 11 come into electrically conductive contact with the flange or frame to thus substantially reduce the volume resistivity of the electrically conductive portion 20, this further making it possible to use a carrier 27 of a non-conductive material, such as plastics, for example.

Referring now to Fig. 3 there is illustrated how the sealing profile 40 comprises a hollow chamber 18 in the anti-trap guard portion 32. Arranged in the hollow chamber 18 are the electrically conductive portions 19, 20, the portion 20 contacting the carrier 17. Deformation of the hollow chamber 18 brings the portions 19, 20 into contact with each other in triggering the switching action as described above.

At the same time the hollow chamber 18 of the anti-trap guard portion 32 serves to seal off a powered closing device (not shown in Fig. 3). More particularly the sealing profile 40 as shown in Fig. 3 can be put to use to weatherseal an automotive sunroof.

Referring now to Fig. 4 there is illustrated a sealing profile 50 in accordance with the invention which is inserted into a substantially U-shaped frame 51 made of an electrically conductive material. The sealing profile 50 comprises a series of lips 52 having a friction-reducing coating 23 for sealing contact with the window pane 25. Tabs 53, 54 serve to secure the sealing profile 50. The electrically conductive portion 20 of the anti-trap guard portion 32 clasps the frame 51 in part and extends up to the outer side of the sealing profile 50.

The sealing profiles 10, 30, 50 as shown in Figs. 1, 2 and 4 are particularly suitable for weathersealing automotive side windows. Referring now to Fig. 5 there is illustrated a system diagram of the sealing profile 30 in the fitted condi-

tion. The sealing profile 30 is mounted on a flange 26 by its clamping portion 11. The flange 26 is thus in electrically conductive contact with the electrically conductive portion 20 via the lips 15 and protuberances 16. As is usual in automotive applications, the flange 26 is grounded, whilst the electrically conductive portions 19 of the sealing profile 30 is connected to the anode of a voltage source (not shown). As soon as the window pane 25 is lifted and the anti-trap guard portion 32 deformed, the two portions 19, 20 come into contact with each other, resulting in a switching action which is signalled to a controller 31. The controller 31 correspondingly controls a motor 29 to move the window pane 25 which halts or reverses the movement of the window pane 25.

The sealing profile 10, 30, 40, 50 in accordance with the invention permits total elimination of one of the metallic conductors hitherto required, without detracting the anti-trap guard and sealing function. Instead, the space requirement, weight, costs and complications in production are all substantially reduced, as compared to known sealing profiles.

Claims

1. A shaped seal (10; 30; 40; 50) for sealing a power-operated closing device (25), including an anti-trap guard (32) comprising at least two electrically conductive portions (19, 20) spaced away from each other, whose contact triggers a switching action for activating the drive assembly (29) of said closing device (25), at least one of said portions (19, 20) being electrically conductive connected to a metallic conductor (17; 26; 27; 51) to reduce the volume resistivity, characterized in that said metallic conductor is configured as a carrier (17; 27) for securing said shaped seal (10; 30; 40) and/or as a flange (26) or frame (51) to which said shaped seal (10; 30; 40; 50) is securable
2. The shaped seal as set forth in claim 1, characterized in that said carrier (17) contacts said electrically conductive portion (20).
3. The shaped seal as set forth in claim 1, characterized in that said carrier (17; 27) is surrounded partly or fully by said electrically conductive portion (20).
4. The shaped seal as set forth in any of the claims 1 to 3, characterized in that said carrier (27) is provided with recesses (28).
5. The shaped seal as set forth in any of the claims 1 to 4, characterized in that said electrically conductive portion (20) extends up to the outer side of said shaped seal (30; 50).
6. The shaped seal as set forth in claim 5, characterized in that said electrically conductive portion (20) comprises lips (15) or tabs (54) for securing said shaped seal (30) to said flange (26) or to said frame (51).

7. The shaped seal as set forth in any of the claims 1 to 6, characterized in that said anti-trap guard portion (32) comprises a hollow chamber (18) in which at least one of said electrically conductive portions (19; 20) is arranged.
8. The shaped seal as set forth in claim 7, characterized in that said hollow chamber serves to seal said powered closing device (25).
9. The shaped seal as set forth in any of the claims 1 to 8, characterized in that said electrically conductive portion (19) provided separate from said carrier (17; 27), said flange (26), or said frame (51) comprises a metallic conductor (22).